

Hematology Analyzer 3 Part Diff

VERCENTRA HA-30



VIRTUEDX

ecatalogue



Throughput

60 sampel/jam

Prinsip kerja

Impedansi untuk WBC, RBC, PLT
Metode kolorimetri non-Sianida
untuk HGB

Parameter

24 Parameter:
WBC, Lym#, Mid#, Gran#, Lym%,
Mid%, Gran%, NLR, PLR, RBC,
HGB, HCT, MCV, MCH, MCHC,
RDW-CV, RDW-SD, PLT, MPV,
PDW-CV, PDW-SD, PCT, P-LCC,
P-LCR

Histogram

3 Histogram (WBC, RBC, PLT)

Volume Sampel

Whole blood mode: 9 μ l
Capillary mode: 9 μ l
Prediluted mode: 20 μ l

Kalibrasi

Kalibrasi manual
Kalibrasi otomatis
Kalibrasi fresh blood

Kontrol Kualitas

3-Level QC
L-J QC
X-B QC

Diproduksi oleh:
PT. VIRTUE DIAGNOSTICS INDONESIA

Kawasan Industri Jababeka 7, Kav. B3B
Cikarang Utara, Kab. Bekasi, Jawa Barat 17534

Telp: 021 38725029
Email: customerservice.id@virtuedx.com
Website: virtuedx.co.id

Reagen

Diluent, Lyse, Probe cleaner

Cetak

Auto print, Manual print

Komunikasi

Support Bi-directional LIS

Bahasa

Bahasa Indonesia
Bahasa Inggris

Input dan output

10,4 inch touch screen
Internal printer
Support external printer

Interface

USB port, Network port

Penyimpanan data

600.000 hasil pemeriksaan
dengan histogram

Dimensi

430mm x 280mm x 400mm
(PxLxT)

Berat

17,5kg

Lingkungan kerja

Rentang suhu lingkungan 10-30°C,
Kelembapan \leq 70%, 100-240V,
50/60Hz, 160VA, 70kPa-106kPa